



PRODUCT INFORMATION

JT 1256 Double-coated Tape

Features/characteristics

1. Adhesive: Acrylic (solvent base) adhesive coated on both sides.
2. Carrier: 2 mil Un-plasticized PVC film.
3. Liner: 3 mil #60 (90 g/m²) Glassine release liner, Mustard color.
4. High peel adhesion and high grab tack that provides bonding quickly.
5. Good resistance against to solvent, chemical, UV & heat.

Technical data

1. Thickness: 9mil total
2. Loop Tack: FINAT-9 98.76 oz/ inch (2.8 kg/ 25mm)
3. Peel Adhesion: PSTC-1 91.70 oz/ inch (2.6 kg/ 25mm)
4. Shear Strength: PSTC-7 Over 72 hrs with 35.2 oz loading on 1" x 1" (1.0 kg/ 25mm X 25mm) holding of 2 stainless steel plates at 77 °F (25 °C)
5. Heat Resistance: Over 24 hrs with 17.6 oz loading on 1" x 1" (0.5 kg/ 25 mm x 25 mm) holding of 2 stainless steel plates at 158 °F (70 °C)
6. Service Temperature: -4 °F ~ 194 °F (-20 °C ~ 90 °C)
7. Tensile Strength: MD: 15.4 lb/in MD: 9.9 lb/in
8. Elongation: MD: 161 % TD: 118 %

Applications

1. Permanent bonding result to most substrates, such as Metal, Wood, Glass, Cement & Plastics.
2. Main application: fixing to the decorative trim, such as PVC profile for Furniture Industry.
3. Fastening for Nameplates, Trophy, Luggage Tag, & Labels.

Shelf Life: Two years from date of receipt by customer when stored at 72 °F (22 °C) and 50% relative humidity.

Remark

All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.

It's essential that the user should evaluate the product for a period of time to determine whether it is fit for a particular purpose and suitable for the user's method of application.